

# DOUBLE DOOR. A60

Art nr: MV4361WG

**MOME C**  
DOORS OF SWEDEN



Fire rated hinge double door special made for use in a maritime environment. Weather- and gastight. Medium duty doors.

Fire class:	A60
Door leaf:	Made of 1,5 mm steel and insulated with mineral wool. Standard is powder coating in RAL 9010.
Thickness of door leaf:	62 mm
Frame:	Steel 4 mm. Silicone gasket four sides.
Hinges:	Stainless steel, 3 pcs
Striker plate:	Stainless steel
Max. clear opening:	W 2000 H 2100 mm
Norsok door type code:	M1/M2



The door are tested according to IMO 2010 FTP Code

## OPTIONS

- Wet paint, laminated or plastic coated.
- Cover plate made in stainless steel for the sill.
- Kick/trolley plate made in stainless steel. H 300/800 mm.
- Air- and gas tightness.
- Vision panel max W400 x H600 mm.
- Panic device
- Hose port
- Electric access control systems
  - Door open system
  - Hold open system
  - Door sensor



OPTION EXAMPLE  
Vision Panels. Hose port.

## DOOR SPAREPARTS

We provide all the necessary accessories for our doors.  
Please contact our service department at:

Mail: [service@momec.se](mailto:service@momec.se) | Phone: +46 734 42 55 87

Gaskets  
Hinges  
Handles  
Lock Cases  
Door Closers  
Cylinders  
Window Panels  
Accessories

