

# SINGLE DOOR. B15 WITH TOPMODULE

Art nr: MV2255M

**MOME C**  
DOORS OF SWEDEN



Fire rated hinge door special made for internal use in a maritime environment. Light duty door.

Fire class:	B15
Door leaf:	Made of steel and insulated with mineral wool. Standard is powder coating in RAL 9010
Thickness of door leaf:	38 mm
Frame:	Steel 1,5
Hinges:	Stainless steel, 3 pcs
Striker plate:	Stainless steel
Sill cover:	Stainless steel
Max. clear opening:	W 1000 x H 2000 mm
Max. height with top panel:	H 2476 mm
Norsok door type code:	L1/L2



The door are tested according to IMO 2010 FTP Code

## OPTIONS

- Laminated or pvc coated, stainless steel
- Kick/trolley plate made in stainless steel. H 300/800 mm.
- Vision panel max W400 x H600 mm.
- Panic device
- Kick-out panel 450 x 450 mm
- Ventilation grid 200 cm<sup>2</sup>
- Electric access control systems
  - Door open system
  - Hold open system
  - Door sensor



OPTION EXAMPLE  
Ventilation grill.

## DOOR SPAREPARTS

We provide all the necessary accessories for our doors.  
Please contact our service department at:

Mail: [service@momec.se](mailto:service@momec.se) | Phone: +46 734 42 55 87

Gaskets  
Hinges  
Handles  
Lock Cases  
Door Closers  
Cylinders  
Window Panels  
Accessories

